

British Manufacturing since 1957



The Professionals Choice

WMSP3W

SureFlow Plus Wall Mount Water Boiler White



FULL SPECIFICATION



WMSP3W Wall Mounted SureFlow Plus Auto Fill Water Boiler – White Case

Туре	Premium Wall Mount – Wall mount Water Boiler
Country of Design & Manufacture	UK
CAPACITY, WEIGHTS & DIMENSIONS:	
	2
Capacity (Litres)	3 332 x 210 x 452
Unit dimensions (W x D x H) mm	590 x 440 x 700
Packed dimensions (W x D x H) mm	90mm
Tap protrusion mm	7.3
Product weight - empty (kg)	12.5
Product weight – full (kg)	11.2
Packed weight (kg)	11.2
CONSTRUCTION:	White Plastic FRABS
Outer fabrication (body) construction Tank construction	
Tank wall thickness	304 & 316 grade Stainless Steel
	0.9mm
ELECTRICAL:	2
Power rating (kW)	3
Voltage supply Electrical supply	230 V (50-60Hz)
Electrical Supply Electrical Connection	Single-phase, N & E (min break rating of 13amp required) Wire into double-pole fused spare (minimum cable size:
Electrical Connection	1.5mm ²). Use of an ELCB is recommended
DILIMPING	1.5IIIII1²). Ose of all ELOB is reconfinenced
PLUMBING: Water inlet connection:	2//" DCD or 15mm puch fit
	3/4" BSP or 15mm push-fit 2 – 7 bar (28psi – 100psi)
Mains water pressure range Overflow/waste connection:	15mm push-fit (extend if required: pipework to have a
Overnow/waste connection.	continuous fall (no longer than 500mm), no more than 3
	right-angle bends.
PERFORMANCE:	nghe angle bends.
Water temperature delivered	96°C (default) – can be adjusted if required
Heat up time to working temperature	11 mins (full tank capacity)
Output per hour (@ default temperature setting)	28 Litres (higher output/hour if set @ lower temperature)
Rapid draw-off	3 Litres
Recovery per minute	0.5 Litres
Stand-by power loss (idle mode)	0.076 kW/h
FILTRATION:	0.07 0 (0.07)
Multi-Filter (taste & odour, sediment & reduces lime-scale)	No (available as an optional extra if required)
OTHER FEATURES:	(available de all optional extra li required)
7 day programmable timer	Yes
Energy-saving ECO mode	No
Tank-baffle plates – unique design aids heat recovery &	Yes
reduces steam emissions to atmosphere	. ••
Early warning lime-scale diagnostics (via LCD display)	Yes
Dual safety protection	Yes - Over-boil & boil-dry protection
STANDARDS & APPROVALS:	
WRAS approved	Yes
EMC Tested and Certified (EN 55014 & EN 61000)	Yes
Electrical Safety Tested and Certified to BS standard	Yes
EN 60335-1 & 2	
WARRANTY & AFTER-SALES:	
Guarantee	2 Year parts & labour
Spare parts, filters & accessories	Same day despatch (if ordered before 3pm)
, , ,	

Instanta Limited

T: 01704 501114 F: 01704 501115 E: <u>sales@instanta.com</u>





Certificate Numbers: FM01234 & EM01234